



---

## Numerics

- 2.4-GHz WMIC, contrasted with 4.9-GHz WMIC [1-8](#)
- 802.11g [3-6, 3-9](#)
- 802.1x authentication [4-13](#)

---

## A

### AAA

- server group [4-25](#)
- aaa authentication login command [4-24](#)
- aaa authorization command [4-27](#)
- aaa new-model command [4-22, 4-25](#)
- abbreviating commands [A-4](#)
- access point
  - security settings, matching client devices [8-24](#)
  - WDS [9-1](#)
- accounting
  - with RADIUS [4-28](#)
  - with TACACS+ [4-32, 4-37](#)
- accounting command [5-2](#)
- administrator access [4-21](#)
- Advanced Encryption Standard (AES) [1-7](#)
- AES-CCMP [8-1](#)
- Aironet 802.11 extensions [4-40](#)
- Aironet Client Utility (ACU) [17-3](#)
- antenna gains [B-4](#)
- antennas [3-13](#)
- ARPANET [4-1](#)
- attributes, RADIUS
  - vendor-proprietary [4-30](#)
  - vendor-specific [4-29](#)
- authentication

- EAP server [4-20, 8-3](#)
- local mode with AAA [4-38](#)
- MAC address [8-5](#)
- NTP associations [4-47](#)
- RADIUS
  - key [4-22](#)
  - login [4-24](#)
  - server configuration for fast secure roaming [9-5](#)
- TACACS+
  - defined [4-32](#)
  - key [4-34](#)
  - login [4-34, 4-35](#)
- authentication network-eap command [9-10](#)
- authentication types
  - CCKM key management [8-5](#)
  - EAP-FAST [8-4](#)
  - EAP-TLS [8-4](#)
  - EAP-TTLS [8-5](#)
  - MAC address [8-5](#)
  - matching on root devices and non-root bridges [8-24](#)
  - Network-EAP [8-3](#)
  - open [8-1](#)
  - shared key [8-2](#)
  - using WPA key management [8-6](#)
- authorization
  - with RADIUS [4-27](#)
  - with TACACS+ [4-32, 4-36](#)
- autoinstall [5-2](#)

---

## B

- banner login command [4-5](#)
- banner motd command [4-4](#)

- banners
    - configuring
      - login [4-5](#)
      - message-of-the-day login [4-4](#)
    - default configuration [4-3](#)
    - when displayed [4-3](#)
  - basic data rate [3-1](#)
  - basic settings
    - checking [17-2](#)
  - beacon period command [3-18](#)
  - blocking communication between clients [3-16](#)
  - bootloader [17-7](#)
  - BOOTP [4-2](#)
  - BR350 interoperability [6-2](#)
  - bridge-group command [3-17, 6-9](#)
  - Bridge Group Virtual Interface (BVI) [2-3](#)
  - bridge interoperability [6-2](#)
  - bridge protocol data unit (BPDU) [6-1](#)
  - BSSIDs [5-3](#)
- 
- C
- carrier busy test [3-21](#)
  - CCKM [8-5](#)
  - CDMA [1-1](#)
  - CDP
    - disabling for routing device [13-4](#)
    - enabling and disabling [13-4](#)
    - monitoring [13-5](#)
  - Centralized Key Management (CCKM) [8-1](#)
  - certificates
    - configuring [8-6](#)
  - channel
    - spacing [3-7, 3-9](#)
  - channel command [3-7](#)
  - channel data rates [3-8, 3-10](#)
  - channel settings [3-6](#)
  - cipher suites
    - enabling [8-5](#)
    - with WPA [8-8](#)
  - Cisco Centralized Key Management
    - See* CCKM
  - Cisco Centralized Key Management (CCKM) [1-7](#)
  - Cisco IOS image release [1-8](#)
  - Cisco IOS image upload [A-9](#)
  - Cisco TAC [17-1](#)
  - CiscoWorks 2000 [14-4](#)
  - CKIP [1-7](#)
  - CKIP (Cisco Key Integrity Protocol) [8-2](#)
  - CLI
    - abbreviating commands [A-4](#)
    - command modes [A-2](#)
    - editing features
      - enabling and disabling [A-6](#)
      - keystroke editing [A-7](#)
      - wrapped lines [A-8](#)
    - error messages [A-4](#)
    - filtering command output [A-9](#)
    - getting help [A-3](#)
    - history
      - changing the buffer size [A-5](#)
      - described [A-5](#)
      - disabling [A-6](#)
      - recalling commands [A-5](#)
      - no and default forms of commands [A-4](#)
  - client communication, blocking [3-16](#)
  - clock
    - See* system clock
  - clock set command [4-44](#)
  - clock timezone command [4-45](#)
  - CMIC [1-7, 8-2](#)
  - CMIC (Cisco Message Integrity Check)
    - See* CMIC
  - command-line interface
    - See* CLI
  - command modes [A-2](#)
  - commands
    - aaa authentication login [4-24](#)

- aaa authorization 4-27
- aaa new-model 4-22, 4-25
- abbreviating A-4
- accounting 5-2
- authentication network-eap 9-10
- banner login 4-5
- banner motd 4-4
- beacon period 3-18
- bridge-group 3-17, 6-9, 10-4
- cdp enable 13-4
- cdp holdtime 13-3
- cdp timer 13-3
- channel 3-7
- clear cdp counters 13-5
- clear cdp table 13-5
- client profile multiple 6-5
- clock set 4-44
- clock timezone 4-45
- concatenation 3-14
- del 17-4
- distance 3-15
- dot11 interface speed 9-11
- encapsulation 10-3
- encapsulation dot1q 10-4
- encryption 6-5
- encryption mode cipher 8-1
- fragment-threshold 3-19
- hostname 4-1
- infrastructure-client 3-16
- infrastructure SSID 5-2
- interface dot11radio 6-1
- interface dot11radio0 10-3
- interface fastEthernet0.x 10-4
- ip domain-lookup 4-3
- ip domain-name 4-2
- ip name-server 4-2
- login authentication 4-25
- no and default A-4
- ntp authenticate 4-47
- ntp peer 4-49
- packet retries 3-19
- parent 3-20
- parent timeout 3-20
- payload-encapsulation 3-14
- power 3-5, 3-8
- prompt 4-1
- radius-server host 4-23
- rts 3-18
- rts retries 3-18
- set 17-6
- set BOOT 17-6
- setting privilege levels 4-10
- show cdp 13-5
- show cdp entry 13-5
- show cdp interface 13-5
- show cdp neighbors 13-5
- show cdp traffic 13-5
- show controller dot11radio 3-4
- show dot11 carrier busy 3-21
- spacing 3-7, 3-9
- speed 3-1, 3-3
- ssid 6-1
- tftp\_init 17-5
- vlan 5-2
- community strings
  - configuring 14-5
  - overview 14-4
- concatenation 3-18, 3-19
- concatenation command 3-14
- configuration files
  - creating using a text editor 15-9
  - deleting a stored configuration 15-18
  - downloading
    - preparing 15-10, 15-12, 15-15
    - reasons for 15-8
    - using FTP 15-12
    - using RCP 15-16
    - using TFTP 15-10

- guidelines for creating and using 15-8
- invalid combinations when copying 15-4
- types and location 15-9
- uploading
  - preparing 15-10, 15-12, 15-15
  - reasons for 15-8
  - using FTP 15-14
  - using RCP 15-17
  - using TFTP 15-11
- connections, secure remote 4-39
- console cable 2-1
- console port
  - cable 2-2
- cryptographic message integrity 8-2
- crypto pki CLI 8-6
- crypto software image 4-39

---

## D

- data rate
  - basic 3-1
  - setting 3-1
  - throughput 3-2
- data rates 3-8, 3-10
- date
  - See* NTP and system clock
- daylight saving time 4-46
- default
  - commands A-4
  - configuration, resetting 17-3
- default configuration
  - banners 4-3
  - DNS 4-2
  - NTP 4-47
  - password and privilege level 4-6
  - SNMP 14-5
  - system message logging 16-3
  - TACACS+ 4-33
- del command 17-4

- Delivery Traffic Indication Message (DTIM) 5-3
- DHCP 2-3, 4-2
- directories
  - changing 15-3
  - creating and removing 15-4
  - displaying the working 15-3
- distance command 3-15
- distance setting 3-15
- DNS
  - default configuration 4-2
  - display configuration 4-3
  - overview 4-2
  - setting up 4-2
- domain names
  - DNS 4-2
- Domain Name System
  - See* DNS

- dot11 interface speed command 9-11
- downloading
  - configuration files
    - preparing 15-10, 15-12, 15-15
    - reasons for 15-8
    - using FTP 15-12
    - using RCP 15-16
    - using TFTP 15-10
  - image files
    - deleting old image 15-21
    - preparing 15-19, 15-22, 15-27
    - reasons for 15-18
    - using FTP 15-23
    - using RCP 15-29
    - using TFTP 15-20

---

## E

- editing features
  - enabling and disabling A-6
  - keystrokes used A-7
  - wrapped lines A-8

- EIRP [B-4](#)
  - enable password [4-7](#)
  - enable secret password [4-7](#)
  - encrypted software image [4-39](#)
  - encryption for passwords [4-7](#)
  - encryption mode cipher command [8-1](#)
  - Enhanced Distributed Channel Access (EDCA) [1-7](#)
  - error messages
    - during command entry [A-4](#)
    - setting the display destination device [16-5](#)
    - severity levels [16-7](#)
    - system message format [16-2](#)
  - Ethernet encapsulation [3-14](#)
  - Ethernet indicator [17-1](#)
  - Ethertype protocols
    - protocols
      - Ethertype [C-2](#)
  - Express Security page [2-4](#)
  - Extensible Authentication Protocol
    - See* EAP
  - extensions, Aironet [4-40](#)
- 
- F
- Fast Ethernet Switch mobile interface card (FESMIC) [2-1](#)
  - fast secure roaming
    - and WDS [9-4](#)
    - authentication server [9-5](#)
  - features [1-7](#)
  - files
    - copying [15-4](#)
    - deleting [15-5](#)
    - displaying the contents of [15-7](#)
    - tar
      - creating [15-5](#)
      - displaying the contents of [15-6](#)
      - extracting [15-7](#)
      - image file format [15-19](#)
  - file system
    - displaying available file systems [15-1](#)
    - displaying file information [15-3](#)
    - local file system names [15-1](#)
    - network file system names [15-4](#)
    - setting the default [15-3](#)
  - filtering
    - show and more command output [A-9](#)
  - filters
    - configuring using CLI [12-2](#)
    - protocol [C-1](#)
  - Flash device [15-1](#)
  - forward-delay time [6-6](#)
  - fragmentation threshold [3-19](#)
  - fragment-threshold command [3-19](#)
  - frequencies [B-2](#)
  - FTP
    - accessing MIB files [D-2](#)
    - configuration files
      - downloading [15-12](#)
      - overview [15-11](#)
      - preparing the server [15-12](#)
      - uploading [15-14](#)
    - image files
      - deleting old image [15-26](#)
      - downloading [15-23](#)
      - preparing the server [15-22](#)
      - uploading [15-26](#)
- 
- G
- get-bulk-request operation [14-2](#)
  - get-next-request operation [14-2, 14-4](#)
  - get-request operation [14-2, 14-4](#)
  - get-response operation [14-2](#)
  - global configuration mode [A-3](#)
  - GPRS [1-4](#)
  - group key updates [8-22](#)

## H

- help, for the command line [A-3](#)
- history
  - changing the buffer size [A-5](#)
  - described [A-5](#)
  - disabling [A-6](#)
  - recalling commands [A-5](#)
- history table, level and number of syslog messages [16-8](#)
- host name, ARPANET rules [4-1](#)
- hostname command [4-1](#)

## I

- image, operating system [17-5](#)
- indicators [17-1](#)
- infrastructure-client command [3-16](#)
- infrastructure SSID command [5-2](#)
- inter-client communication, blocking [3-16](#)
- interface configuration mode [A-3](#)
- Interior Gateway Protocol (IGP) [1-4](#)
- IP address [2-3](#)
  - release and renew [2-1](#)
- ip domain-lookup command [4-3](#)
- ip domain-name command [4-2](#)
- ip name-server command [4-2](#)
- IP port protocols [C-4](#)
- IP protocols
  - protocols
    - IP [C-3](#)
- ISO designators for protocols [C-1](#)

## K

- KCK [GL-4](#)
- KEK [GL-4](#)
- key features [1-7](#)
- key management types [8-8](#)

## L

- LEAP
  - setting on client and access point [8-24](#)
- LED indicators
  - Ethernet [17-1](#)
  - radio traffic [17-1](#)
  - status [17-1](#)
- Load balancing [4-40](#)
- login authentication
  - with RADIUS [4-24](#)
  - with TACACS+ [4-34, 4-35](#)
- login authentication command [4-25](#)
- login banners [4-3](#)
- log messages
  - See* system message logging

## M

- MAC address
  - authentication [8-5](#)
  - troubleshooting [17-3](#)
- management options
  - CLI [A-1](#)
- memory
  - Flash [15-1](#)
- Message Authentication Code [GL-5](#)
- Message Integrity Check
  - See* MIC
- Message Integrity Code (MIC), definition [GL-5](#)
- message-of-the-day (MOTD) [4-3](#)
- messages
  - to users through banners [4-3](#)
- method list [4-21](#)
- MIBs
  - accessing files with FTP [D-2](#)
  - location of files [D-2](#)
  - overview [14-1](#)
  - SNMP interaction with [14-4](#)

MIC [4-40, 8-1, 17-3](#)

MoIP tunnel [1-5](#)

monitoring, CDP [13-5](#)

multicast [3-15](#)

multiple basic SSIDs (multiple BSSIDs)

description [5-3](#)

requirements and guidelines [5-3](#)

multiple client profiles

configuring WMIC [6-3, 6-5](#)

description [6-1](#)

## N

name-to-address translation [4-3](#)

Network-EAP [8-3](#)

Network Time Protocol

*See* NTP

no commands [A-4](#)

non-root bridge

infrastructure SSID [5-2](#)

NTP

associations

authenticating [4-47](#)

enabling broadcast messages [4-50](#)

peer [4-49](#)

server [4-49](#)

default configuration [4-47](#)

displaying the configuration [4-54](#)

overview [4-41](#)

restricting access

creating an access group [4-52](#)

disabling NTP services per interface [4-53](#)

source IP address, configuring [4-54](#)

stratum [4-41](#)

synchronizing devices [4-49](#)

time

synchronizing [4-41](#)

ntp authenticate command [4-47](#)

ntp peer command [4-49](#)

## O

OFDM [1-8](#)

## P

packet retries command [3-19](#)

pairwise [GL-5](#)

Pairwise Master Key (PMK) [GL-5](#)

parent command [3-20](#)

parent timeout command [3-20](#)

password reset [17-3](#)

passwords

default configuration [4-6](#)

encrypting [4-7](#)

setting

enable [4-6](#)

enable secret [4-7](#)

with usernames [4-9](#)

payload-encapsulation command [3-14](#)

per-VLAN Spanning Tree (PVST) [6-2](#)

PKI

ports, protected [3-17](#)

power level, maximum [B-4](#)

preamble [3-12](#)

preferential treatment of traffic

*See* QoS

pre-shared key [8-22](#)

primary intersection [1-3](#)

privileged EXEC mode [A-2](#)

privilege levels

exiting [4-11](#)

logging into [4-11](#)

overview [4-5, 4-10](#)

setting a command with [4-10](#)

prompt command [4-1](#)

protocol filters [12-2, C-1](#)

protocols

IP port [C-4](#)

public key infrastructure

*See* PKI

Public Secure Packet Forwarding [3-16](#)

## Q

### QoS

configuration guidelines [11-4](#)

impact on wireless LAN [11-2](#)

overview [11-1](#)

precedence [11-2](#)

quality of service

*See* QoS

## R

### radio

configuring channel settings [3-6](#)

configuring transmit power [3-5](#)

distance setting [3-15](#)

indicator [17-1](#)

radio frequency data rates [3-8, 3-10](#)

radio management [9-1](#)

### RADIUS

administrator access [4-21](#)

attributes

vendor-proprietary [4-30](#)

vendor-specific [4-29](#)

configuring

accounting [4-28](#)

authentication [4-24](#)

authorization [4-27](#)

communication, global [4-22, 4-28](#)

communication, per-server [4-21, 4-22](#)

multiple UDP ports [4-22](#)

default configuration [4-21](#)

defining AAA server groups [4-25](#)

displaying the configuration [4-31](#)

identifying the server [4-21](#)

limiting the services to the user [4-27](#)

method list [4-21](#)

operation of [4-20](#)

overview [4-19](#)

SSID [5-2](#)

suggested network environments [4-19](#)

tracking services accessed by user [4-28](#)

radius-server host command [4-23](#)

range [3-2](#)

rate limit, logging [16-9](#)

### RCP

configuration files

downloading [15-16](#)

overview [15-14](#)

preparing the server [15-15](#)

uploading [15-17](#)

image files

deleting old image [15-30](#)

downloading [15-29](#)

preparing the server [15-27](#)

uploading [15-31](#)

regulatory domains [B-2](#)

release and renew the IP address [2-1](#)

reloading access point image [17-5](#)

Remote Authentication Dial-In User Service

*See* RADIUS

Remote Copy Protocol

*See* RCP

request to send (RTS) [3-18](#)

restricting access

NTP services [4-52](#)

passwords and privilege levels [4-5](#)

TACACS+ [4-32](#)

### RFC

1157, SNMPv1 [14-2](#)

1305, NTP [4-41](#)

1901, SNMPv2C [14-2](#)

1902 to 1907, SNMPv2 [14-2](#)

roaming, fast secure roaming using CCKM [9-2](#)



- root port [6-1](#)
  - rts command [3-18](#)
  - rts retries command [3-18](#)
- ## S
- 
- secondary intersection [1-3](#)
  - secure remote connections [4-39](#)
  - Secure Shell
    - See* SSH
  - Secure Shell (SSH)
    - See* SSH
  - security [2-4](#)
    - protocol [4-21](#)
    - root device and non-root bridge settings [8-24](#)
    - synchronizing [8-24](#)
    - troubleshooting [17-3](#)
  - security settings, Express Security page [2-4](#)
  - self-healing wireless LAN [9-4](#)
  - sequence numbers in log messages [16-6](#)
  - server group
    - AAA [4-25](#)
  - set BOOT command [17-6](#)
  - set command [17-6](#)
  - set-request operation [14-4](#)
  - severity levels, defining in system messages [16-7](#)
  - shared-key authentication [8-2](#)
  - show controller dot11radio command [3-4](#)
  - show dot11 carrier busy command [3-21](#)
  - show vlan [10-6](#)
  - Simple Network Management Protocol
    - See* SNMP
  - SNMP
    - accessing MIB variables with [14-4](#)
    - agent
      - described [14-3](#)
      - disabling [14-5](#)
    - community strings
      - configuring [14-5](#)
      - overview [14-4](#)
      - configuration examples [14-9](#)
      - default configuration [14-5](#)
      - limiting system log messages to NMS [16-8](#)
      - manager functions [14-2](#)
      - MIBs, location of [D-2](#)
      - overview [14-1, 14-4](#)
      - snmp-server view [14-9](#)
      - status, displaying [14-10](#)
      - system contact and location [14-9](#)
      - trap manager, configuring [14-8](#)
      - traps
        - described [14-2](#)
        - enabling [14-7](#)
        - overview [14-1, 14-4](#)
        - types of [14-7](#)
        - versions supported [14-2](#)
  - software images
    - delete from Flash [17-5](#)
    - location in Flash [15-18](#)
    - tar file format, described [15-19](#)
  - spacing command [3-7, 3-9](#)
  - spanning-tree
    - root port [6-1](#)
  - Spanning Tree Protocol (STP) [6-1](#)
  - speed command [3-1, 3-3](#)
  - SSH
    - crypto software image [4-39](#)
    - described [4-39](#)
    - description [2-2](#)
    - displaying settings [4-40](#)
    - SSH Communications Security, Ltd. [2-2](#)
  - SSID
    - 2.4-GHz radio [5-2](#)
    - configuring [5-2](#)
    - default (tsunami) [17-2](#)
    - default configuration [5-2](#)
    - disable [5-2](#)
    - infrastructure SSID [5-2](#)

- RADIUS 5-2
  - troubleshooting 17-2
  - understanding 5-1
  - VLAN 2-4, 4-12, 5-3
  - without VLANs 4-11
  - static WEP 4-11
    - with open authentication, setting on client and access point 8-24
    - with shared key authentication, setting on client and access point 8-24
  - statistics
    - CDP 13-5
    - SNMP input and output 14-10
  - status indicators 17-1
  - STP
    - BPDU message exchange 6-2
    - designated port, defined 6-3
    - designated switch, defined 6-3
    - displaying status 6-14
    - inferior BPDU 6-3
    - interface states
      - blocking 6-6
      - disabled 6-7
      - forwarding 6-6, 6-7
      - learning 6-7
      - listening 6-7
      - overview 6-5
    - overview 6-1
    - root port, defined 6-3
    - timers, described 6-4
  - stratum, NTP 4-41
  - summer time 4-46
  - switchport protected command 3-17
  - syslog
    - See* system message logging
  - system clock 4-41
    - configuring
      - daylight saving time 4-46
      - manually 4-44
      - summer time 4-46
      - time zones 4-45
    - displaying the time and date 4-44
    - overview 4-41
    - See also* NTP
  - system message logging
    - default configuration 16-3
    - defining error message severity levels 16-7
    - disabling 16-4
    - displaying the configuration 16-11
    - enabling 16-4
    - facility keywords, described 16-11
    - level keywords, described 16-8
    - limiting messages 16-8
    - message format 16-2
    - overview 16-1
    - rate limit 16-9
    - sequence numbers, enabling and disabling 16-6
    - setting the display destination device 16-5
    - timestamps, enabling and disabling 16-6
    - UNIX syslog servers
      - configuring the daemon 16-10
      - configuring the logging facility 16-10
      - facilities supported 16-11
  - system name 4-1
    - manual configuration 4-1
- 
- T
- TAC 17-1
  - TACACS+
    - accounting, defined 4-32
    - authentication, defined 4-32
    - authorization, defined 4-32
    - configuring
      - accounting 4-37
      - authentication key 4-34
      - authorization 4-36
      - login authentication 4-34, 4-35

- default configuration [4-33](#)
  - displaying the configuration [4-38](#)
  - identifying the server [4-34](#)
  - limiting the services to the user [4-36](#)
  - operation of [4-33](#)
  - overview [4-32](#)
  - tracking services accessed by user [4-37](#)
  - tar files
    - creating [15-5](#)
    - displaying the contents of [15-6](#)
    - extracting [15-7](#)
    - image file format [15-19](#)
  - Telnet [2-1, 2-2](#)
  - Temporal Key Integrity Protocol (TKIP) [8-1](#)
  - Terminal Access Controller Access Control System Plus
    - See* TACACS+
  - TFTP [17-5](#)
    - configuration files
      - downloading [15-10](#)
      - preparing the server [15-10](#)
      - uploading [15-11](#)
    - image files
      - deleting [15-21](#)
      - downloading [15-20](#)
      - preparing the server [15-19](#)
      - uploading [15-22](#)
  - tftp\_init command [17-5](#)
  - TFTP server
    - Cisco IOS image upload [A-9](#)
  - throughput [3-2, 3-7](#)
  - time
    - See* NTP and system clock [4-41](#)
  - timestamps in log messages [16-6](#)
  - time zones [4-45](#)
  - TKIP [4-40](#)
  - transmit and receive antennas
    - configuring [3-13](#)
  - transmit power [3-5](#)
  - transmit speed [3-1](#)
  - traps
    - configuring managers [14-7](#)
    - defined [14-2](#)
    - enabling [14-7](#)
    - notification types [14-7](#)
    - overview [14-1, 14-4](#)
  - troubleshooting [17-1](#)
    - with CiscoWorks [14-4](#)
    - with system message logging [16-1](#)
  - tunnel [1-5](#)
- ## U
- 
- universal workgroup bridge
    - and multiple client profiles [6-1](#)
  - UNIX syslog servers
    - daemon configuration [16-10](#)
    - facilities supported [16-11](#)
    - message logging configuration [16-10](#)
  - upgrading software images
    - See* downloading
  - uploading
    - configuration files
      - preparing [15-10, 15-12, 15-15](#)
      - reasons for [15-8](#)
      - using FTP [15-14](#)
      - using RCP [15-17](#)
      - using TFTP [15-11](#)
    - image files
      - preparing [15-19, 15-22, 15-27](#)
      - reasons for [15-18](#)
      - using FTP [15-26](#)
      - using RCP [15-31](#)
      - using TFTP [15-22](#)
  - user EXEC mode [A-2](#)
  - username-based authentication [4-9](#)

## V

## VLAN

- and bridges [10-2](#)
  - configuring [10-3](#)
  - overview [10-1](#)
  - SSID [2-4, 4-11, 4-12, 5-3](#)
  - with wireless bridges [10-3](#)
- vlan command [5-2](#)

## W

## WDS

- access point [9-1](#)
  - and fast secure roaming [9-4](#)
  - and WMIC [9-1](#)
  - CLI commands [9-9](#)
  - guidelines and requirements [9-4](#)
- web site
- Cisco Software Center [17-7](#)

## WEP

- configuring key [8-2](#)
- described [8-2](#)
- key example [8-5](#)
- key restrictions [8-4](#)
- keys [17-3](#)
- troubleshooting [17-3](#)
- with EAP [8-3](#)

## Wi-Fi Multimedia

*See* WMM

## Wi-Fi Protected Access

*See* WPA

Wi-Fi Protected Access (WPA) [4-13](#)

## Wired Equivalent Privacy

*See* WEP

wireless bridges [10-3](#)

## Wireless Domain Services

*See* WDS

## WMIC

- and WDS [9-1](#)
- Cisco IOS image upload procedure [A-9](#)
- multiple client profiles [6-3, 6-5](#)

## WMM

- workgroup bridge
  - infrastructure SSID [5-2](#)
- world mode
  - 802.11d standard [3-11](#)
  - Cisco legacy [3-11](#)
  - enabling and disabling [3-11](#)

WPA [4-11](#)

- cipher suite [8-1](#)
- description [8-6](#)
- key management [8-6](#)

WPA2 [1-7](#)